

## PRODUCT DATA

## AEROSOLS PAINT STRIPPER 2910

### DESCRIPTION

RUST-OLEUM® Paint Stripper 2910 is a paint dissolving material based on methylene chloride in an aerosol.

### RECOMMENDED USES

RUST-OLEUM Paint Stripper 2910 should be used for quick removal of old paint. RUST-OLEUM Paint Stripper 2910 is intended to remove all types of oil- and alkyd-based paints, emulsion paints, varnish and most two-component materials from metal, mineral and wooden substrates. As RUST-OLEUM Paint Stripper 2910 does not contain acids or alkali's, it will not affect metal, mineral or wooden substrates.

### TECHNICAL DATA

Appearance: White, foamy layer  
VOC-content: 862 g/l

### Coverage

Theoretical: 2-3 m<sup>2</sup> per aerosol.  
Practical: Practical coverage depends on many factors such as type of old coating and shape of the substrate and material losses during application.

### SURFACE PREPARATION

Remove loose coatings as much as possible by scraping.

### DIRECTION FOR USE

Remove cover cap. Shake vigorously before use. Hold the can approx. 10-20 cm from the substrate. Apply a uniform foam layer of Paint Stripper 2910, allow to stand for 5 to 10 minutes, and remove the old layer with a filling knife or paint scraper. Thick layers of some (two-component) products may need an additional treatment. After use, clean the surface with cleaner/degreaser, fresh water or white spirit and allow to dry completely before applying a coating.

### APPLICATION CONDITIONS

Temperature of air, substrate and aerosol between 10 and 35°C and relative humidity below 85%.

### REMARKS

RUST-OLEUM Paint Stripper 2910 may affect plastic materials alike e.g. PVC, polystyrene. In case of doubt, try on a small test patch beforehand.

### SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

### SHELLIFE / STORAGE CONDITIONS

2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

#### Rust-Oleum Netherlands B.V.

Braak 1, 4704 RJ  
P.O. Box 138, 4700 AC  
Roosendaal, The Netherlands  
T +31 (0)165 593 636  
F +31 (0)165 593 600  
[info.nl@ro-m.com](mailto:info.nl@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

#### N.V. Martin Mathys S.A

Kolenbergstraat 23  
B - 3545 Zelem  
Halen, Belgium  
T +32 (0)13 460 200  
F +32 (0)13 460 201  
[info.be@ro-m.com](mailto:info.be@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

#### Rust-Oleum France S.A

11, Rue Jules Verne, B.P. 39  
95322 St-Leu-la-Forêt Cedex  
France  
T +33 (0)130 400 044  
F +33 (0)130 409 980  
[info.fr@ro-m.com](mailto:info.fr@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

#### Rust-Oleum UK Ltd.

Unit 5D, Alexandra Way  
Ashchurch B. Centre,  
Tewkesbury, Gloucestershire  
GL20 8NB, United Kingdom  
T +44 (0)1684 273 333  
F +44 (0)1684 273 331  
[info.uk@ro-m.com](mailto:info.uk@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)

#### Rust-Oleum Mathys Italia s.r.l.

Via Mazzetta 36, 13856  
Vigliano Biellese BI, Italia  
T +39 015 8122 160  
F +39 015 8122 161  
[info.it@ro-m.com](mailto:info.it@ro-m.com)  
[www.ro-m.com](http://www.ro-m.com)