

PRODUCT DATA

FILLCOAT

DESCRIPTION

Waterproofing product based on solvent soluble high polymers.

MAIN PROPERTIES

Instantly waterproof - to 1300% elastic - good resistance against weather influences, mineral acids (max. 10% in water) - not resistant against solvents and alkaline substrates - does not contain bituminous products - excellent adhesion on different substrates.

RECOMMENDED USES

Waterproof finish of roofs, non-walkable terraces, gutters, ridge-pieces, chimney stacks, pipes, etc.

TECHNICAL DATA

Appearance:	Satin gloss (gloss 60°: ± 45%)
Colour:	Light grey - dark grey - black
Density:	1,03 - 1,06 g/cm ³
Solids Content:	In volume: 42 - 44% In weight: 51 - 54%
Recommended film thickness:	Wet film: 1000 micron (cons.: 1 l/m ²) Dry film: 430 micron (cons.: 1 l/m ²)
Flashpoint:	40°C. Flammable
VOC-content:	485 g/l max.
Ready-for-use mixture:	485 g/l max.
Category:	A/i
EU Limit values:	600 g/l (2007) / 500 g/l (2010)

Drying times	20°C/50% r.h.
To touch:	4 hours
To recoat:	3 - 14 days with the same product. 6 weeks with a paint.

Coverage

Theoretical:	1 coat of 1 - 1,5 l/m ² Apply 2 coats in combination with the Dakfill-fleece (see below).
Practical:	Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

SURFACE PREPARATION

Remove dust, mud, grease, moss and withered leaves carefully. The spots to be repaired are cleaned with a hard broom and sponged. After cleaning, Fillcoat can be applied directly on bituminous substrates, hard PVC, polyester, zinc, aluminium, glass, tiles, etc.

Porous materials (concrete, stone, wood) must first be dried and pre-treated with a coat of Primer 44 (30% diluted with Thinner 22).

In case of repeatedly repaired spots, important or active cracks, Fillcoat without fibres is to be reinforced with Dakfill-fleece: apply a coat of Fillcoat (about 1 l/m²), unroll Dakfill-fleece in it and cover it immediately with another coat of Fillcoat.

DIRECTION FOR USE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

Rust-Oleum Netherlands B.V.

Braak 1, 4704 RJ
P.O. Box 138, 4700 AC
Roosendaal, The Netherlands
T +31 (0)165 593 636
F +31 (0)165 593 600
info.nl@ro-m.com
www.ro-m.com

N.V. Martin Mathys S.A.

Kolenbergstraat 23
B - 3545 Zelem
Halen, Belgium
T +32 (0)13 460 200
F +32 (0)13 460 201
info.be@ro-m.com
www.ro-m.com

Rust-Oleum France S.A.S

11, Rue Jules Verne, B.P. 60039
95322 St-Leu-la-Forêt Cedex
France
T +33 (0)130 400 044
F +33 (0)130 409 980
info.fr@ro-m.com
www.ro-m.com

Rust-Oleum UK Ltd.

Unit 6, Spitfire Close
Coventry Business Park
Coventry, CV5 6UR
United Kingdom
T +44 (0)2476 717 329
F +44 (0)2476 718 930
info.uk@ro-m.com
www.ro-m.com

Rust-Oleum Mathys Italia s.r.l.

Largo Donegani 2
20121 Milano, Italia
T +39 335 10 93 482
info.it@ro-m.com
www.ro-m.com

PRODUCT DATA

FILLCOAT

APPLICATION & THINNING

Brush:	Do not dilute.
Roller:	Do not dilute.
Air-atomised spray:	Not recommended
Airless spray:	Do not dilute. Nozzle: 18 - 23 / Pressure: 220 bars.
Cleanup:	Thinner 22 or white spirit.

APPLICATION CONDITIONS

Can be applied during all weather conditions, except for snow.

REMARKS

- Adhesion primer on Dac Alu.
- Recoatable with Dakfill New, Coating PRT or Dac Alu.
- Never apply to polystyrene insulation or onto new concrete.
- **Do not** apply Fillcoat as priming coat under Dac Hydro Alu.

SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

SHELLIFE / STORAGE CONDITIONS

5 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Rust-Oleum Netherlands B.V.

Braak 1, 4704 RJ
P.O. Box 138, 4700 AC
Roosendaal, The Netherlands
T +31 (0)165 593 636
F +31 (0)165 593 600
info.nl@ro-m.com
www.ro-m.com

N.V. Martin Mathys S.A.

Kolenbergstraat 23
B - 3545 Zelem
Halen, Belgium
T +32 (0)13 460 200
F +32 (0)13 460 201
info.be@ro-m.com
www.ro-m.com

Rust-Oleum France S.A.S

11, Rue Jules Verne, B.P. 60039
95322 St-Leu-la-Forêt Cedex
France
T +33 (0)130 400 044
F +33 (0)130 409 980
info.fr@ro-m.com
www.ro-m.com

Rust-Oleum UK Ltd.

Unit 6, Spitfire Close
Coventry Business Park
Coventry, CV5 6UR
United Kingdom
T +44 (0)2476 717 329
F +44 (0)2476 718 930
info.uk@ro-m.com
www.ro-m.com

Rust-Oleum Mathys Italia s.r.l.

Largo Donegani 2
20121 Milano, Italia
T +39 335 10 93 482
info.it@ro-m.com
www.ro-m.com